

**RTV 3oz Silicone Adhesive****SECTION 1. IDENTIFICATION**

Product name : RTV 3oz Silicone Adhesive  
 Product code. : TA2100

**Manufacturer or supplier's details**

Company name of supplier : KIMTECH INC  
 Address : 848 N Rainbow # 2699  
 Las Vegas, NV 89107  
 Telephone : (702) 880-0056  
 Emergency telephone : AAPCC: 1(800)222-1222

**Recommended use of the chemical and restrictions on use**

Recommended use : Adhesive, binding agents

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Not a hazardous substance or mixture.

**GHS Label element**

Not a hazardous substance or mixture.

Precautionary Statements : **Prevention:**  
 P271 Use only outdoors or in a well-ventilated area.

**Other hazards**

None known.

**SECTION 3. COMPOSITION INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture  
 Chemical nature : Silicone elastomer

**Hazardous ingredients**

Chemical Name	CAS-No.	Concentration (%)
Silicon dioxide	7631-86-9	>= 5 - < 10
Distillates (petroleum), hydrotreated middle	64742-46-7	>= 5 - < 10
Titanium dioxide	13463-67-7	>= 1 - < 5
Aluminium	7429-90-5	>= 1 - < 5
Carbon black	1333-86-4	>= 0.1 - < 1

**RTV 3oz Silicone Adhesive**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.1	07/12/2019	1373688-00001	Date of first issue: 02/25/2015

---

**SECTION 4. FIRST AID MEASURES**

If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	: Wash with water and soap as a precaution. Get medical attention if symptoms occur.
In case of eye contact	: Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	: None known.
Protection of first-aiders	: No special precautions are necessary for first aid responders.
Notes to physician	: Treat symptomatically and supportively.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	: Water spray Alcohol-resistant foam Dry chemical Carbon dioxide (CO <sub>2</sub> )
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	: Exposure to combustion products may be a hazard to health.
Hazardous combustion products	: Carbon oxides Silicon oxides Formaldehyde Metal oxides
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	: Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

---

**RTV 3oz Silicone Adhesive**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.1	07/12/2019	1373688-00001	Date of first issue: 02/25/2015

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice. Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers. Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Ingredients with workplace control parameters**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

## RTV 3oz Silicone Adhesive

Version 1.1      Revision Date: 07/12/2019      MSDS Number: 1373688-00001      Date of last issue: -  
 Date of first issue: 02/25/2015

Silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m <sup>3</sup> / %SiO <sub>2</sub> (Silica)	OSHA Z-3
		TWA	6 mg/m <sup>3</sup> (Silica)	NIOSH REL
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA	10 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
Aluminium	7429-90-5	TWA (Respirable)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup>	NIOSH REL
		TWA (total dust)	15 mg/m <sup>3</sup> (Aluminum)	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup> (Aluminum)	OSHA Z-1
		TWA (pyro powders)	5 mg/m <sup>3</sup> (Aluminum)	NIOSH REL
		TWA (Respirable fraction)	1 mg/m <sup>3</sup> (Aluminum)	ACGIH
Carbon black	1333-86-4	TWA	3.5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3.5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable fraction)	3 mg/m <sup>3</sup>	ACGIH

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
 Ensure adequate ventilation, especially in confined areas.  
 Minimize workplace exposure concentrations.  
 Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m<sup>3</sup> - total dust, 5 mg/m<sup>3</sup> - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m<sup>3</sup> - respirable particles, 10 mg/m<sup>3</sup> - inhalable particles.

**Personal protective equipment**

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are

**RTV 3oz Silicone Adhesive**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.1	07/12/2019	1373688-00001	Date of first issue: 02/25/2015

---

unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

**Hand protection**

Remarks : Wash hands before breaks and at the end of workday.

**Eye protection**

: Wear the following personal protective equipment:  
Safety glasses

**Skin and body protection**

: Skin should be washed after contact.

**Hygiene measures**

: Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.  
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: paste
Color	: in accordance with the product description
Odor	: Acetic acid
Odor Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: Not applicable
Flash point	: > 100 °C Method: closed cup
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: No data available

**RTV 3oz Silicone Adhesive**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.1	07/12/2019	1373688-00001	Date of first issue: 02/25/2015

---

Lower explosion limit	: No data available
Vapor pressure	: Not applicable
Relative vapor density	: No data available
Relative density	: 1.007
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: Not applicable
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Acetic acid is formed upon contact with water or humid air. When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required. See OSHA formaldehyde standard, 29 CFR 1910.1048 Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	: None known.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	

## RTV 3oz Silicone Adhesive

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.1	07/12/2019	1373688-00001	Date of first issue: 02/25/2015

---

Thermal decomposition : Formaldehyde

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 10 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

#### Ingredients:

##### **Silicon dioxide:**

Acute oral toxicity : LD50 (Rat): > 3,300mg/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Information taken from reference works and the literature.

Acute inhalation toxicity : LC50 (Rat): > 2.08mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Information taken from reference works and the literature.

Acute dermal toxicity : LD50 (Rabbit): > 5,000mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Information taken from reference works and the literature.

##### **Distillates (petroleum), hydrotreated middle:**

Acute oral toxicity : LD50 (Rat): > 5,000mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.78 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

##### **Titanium dioxide:**

Acute oral toxicity : LD50 (Rat): > 5,000mg/kg

**RTV 3oz Silicone Adhesive**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.1	07/12/2019	1373688-00001	Date of first issue: 02/25/2015

---

Acute inhalation toxicity : LC50 (Rat): > 6.82mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

**Aluminium:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 0.888mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

**Carbon black:**

Acute oral toxicity : LD50 (Rat): > 5,000mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0.0046 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

**Skin corrosion irritation**

Not classified based on available information.

**Ingredients:****Silicon dioxide:**

Result: No skin irritation

Remarks: Information taken from reference works and the literature.

**Titanium dioxide:**

Species: Rabbit

Result: No skin irritation

**Aluminium:**

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Remarks: Based on data from similar materials

**Carbon black:**

Species: Rabbit

Result: No skin irritation

**Serious eye damage / eye irritation**

Not classified based on available information.

**Ingredients:**



**RTV 3oz Silicone Adhesive**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.1	07/12/2019	1373688-00001	Date of first issue: 02/25/2015

---

**Silicon dioxide:**

Result: No eye irritation

Remarks: Information taken from reference works and the literature.

**Titanium dioxide:**

Species: Rabbit

Result: No eye irritation

**Aluminium:**

Species: Rabbit

Result: No eye irritation

Remarks: Based on data from similar materials

**Carbon black:**

Species: Rabbit

Result: No eye irritation

**Respiratory or skin sensitization**

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

**Ingredients:****Silicon dioxide:**

Assessment: Does not cause skin sensitization.

Test Type: Skin: test type not specified

Species: Guinea pig

Remarks: No known sensitizing effect.

Information taken from reference works and the literature.

**Titanium dioxide:**

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse

Result: negative

**Aluminium:**

Routes of exposure: Skin contact

Species: Guinea pig

Result: negative

Remarks: Based on data from similar materials

**Carbon black:**

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

**Germ cell mutagenicity**

Not classified based on available information.

**Ingredients:**

## RTV 3oz Silicone Adhesive

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.1	07/12/2019	1373688-00001	Date of first issue: 02/25/2015

---

### Silicon dioxide:

Genotoxicity in vitro : Result: negative  
Remarks: Information taken from reference works and the literature.

Genotoxicity in vivo : Application Route: Ingestion  
Result: negative  
Remarks: Information taken from reference works and the literature.

Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

### Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Result: negative

### Aluminium:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

### Carbon black:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

### Carcinogenicity

Not classified based on available information.

### Ingredients:

#### Titanium dioxide:

Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Exposure time: 24 Months  
Method: OECD Test Guideline 453  
Result: positive  
Remarks: The mechanism or mode of action may not be relevant in humans.  
The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity -Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

**RTV 3oz Silicone Adhesive**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.1	07/12/2019	1373688-00001	Date of first issue: 02/25/2015

---

**Aluminium:**

Species: Rat  
 Application Route: inhalation (dust/mist/fume)  
 Exposure time: 86 weeks  
 Result: negative

**Carbon black:**

Species: Rat  
 Application Route: Inhalation  
 Exposure time: 2 Years  
 Result: positive  
 Target Organs: Lungs  
 Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity -Assessment : Sufficient evidence of carcinogenicity in inhalation studies with animals

**IARC**

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

Carbon black 1333-86-4

**OSHA**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**Ingredients:****Aluminium:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative  
 Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Mouse  
 Application Route: Ingestion  
 Result: negative

**RTV 3oz Silicone Adhesive**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.1	07/12/2019	1373688-00001	Date of first issue: 02/25/2015

---

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

**Ingredients:****Carbon black:**

Routes of exposure: inhalation (dust/mist/fume)

Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

**Repeated dose toxicity****Ingredients:****Titanium dioxide:**

Species: Rat

NOAEL: 24,000 mg/kg

Application Route: Ingestion

Exposure time: 28 d

Species: Rat

NOAEL: 10mg/m3

Application Route: inhalation (dust/mist/fume)

Exposure time: 2 y

Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

**Carbon black:**

Species: Rat

NOAEL: 1 mg/m3

LOAEL: 7 mg/m3

Application Route: Inhalation

Test atmosphere: dust/mist

Exposure time: 90 d

Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

**Aspiration toxicity**

Not classified based on available information.

**Ingredients:****Distillates (petroleum), hydrotreated middle:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:**

**RTV 3oz Silicone Adhesive**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.1	07/12/2019	1373688-00001	Date of first issue: 02/25/2015

---

**Titanium dioxide:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l  
Exposure time: 72 h

Toxicity to bacteria : EC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

**Aluminium:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 14.6 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0.135 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: No toxicity at the limit of solubility.

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 0.004 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: No toxicity at the limit of solubility.

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 7.1 mg/l  
Exposure time: 28 d

**Carbon black:**

Toxicity to fish : LC0 (Danio rerio (zebra fish)): 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 5,600 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202

Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): 10,000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**RTV 3oz Silicone Adhesive**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.1	07/12/2019	1373688-00001	Date of first issue: 02/25/2015

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.

**SECTION 14. TRANSPORT INFORMATION****International Regulation****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Acetic anhydride	108-24-7	5000	*
Acetic acid	64-19-7	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**RTV 3oz Silicone Adhesive**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.1	07/12/2019	1373688-00001	Date of first issue: 02/25/2015

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Aluminium	7429-90-5	1.6 %
-----------	-----------	-------

**US State Regulations****Pennsylvania Right To Know**

Dimethyl siloxane, hydroxy-terminated	70131-67-8	70 - 90 %
Silicon dioxide	7631-86-9	5 - 10 %
Distillates (petroleum), hydrotreated middle	64742-46-7	5 - 10 %
Iron oxide	1332-37-2	1 - 5 %
Titanium dioxide	13463-67-7	1 - 5 %
Aluminium	7429-90-5	1 - 5 %
Acetic acid	64-19-7	0 - 0.1 %
Acetic anhydride	108-24-7	0 - 0.1 %

**New Jersey Right To Know**

Dimethyl siloxane, hydroxy-terminated	70131-67-8	70 - 90 %
Silicon dioxide	7631-86-9	5 - 10 %
Distillates (petroleum), hydrotreated middle	64742-46-7	5 - 10 %
Iron oxide	1332-37-2	1 - 5 %
Titanium dioxide	13463-67-7	1 - 5 %
Aluminium	7429-90-5	1 - 5 %
Carbon black	1333-86-4	0.1 - 1 %

**California Prop 65**

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

**The ingredients of this product are reported in the following inventories:**

REACH : All ingredients (pre-)registered or exempt.

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

PICCS : All ingredients listed or exempt.

## RTV 3oz Silicone Adhesive

Version 1.1      Revision Date: 07/12/2019      MSDS Number: 1373688-00001      Date of last issue: -  
Date of first issue: 02/25/2015

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List(DSL).


### Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:



#### HMIS III:

<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 NIOSH REL : USA. NIOSH Recommended Exposure Limits  
 OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants-  
1910.1000  
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-  
its for Air Contaminants  
 OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-  
eral Dusts  
 ACGIH / TWA : 8-hour, time-weighted average  
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour  
workday during a 40-hour workweek  
 NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded  
at any time during a workday  
 OSHA P0 / TWA : 8-hour time weighted average  
 OSHA Z-1 / TWA : 8-hour time weighted average  
 OSHA Z-3 / TWA : 8-hour time weighted average

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>



**RTV 3oz Silicone Adhesive**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.1	07/12/2019	1373688-00001	Date of first issue: 02/25/2015

---

Revision Date : 02/25/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8